




Mounting Instructions

Horizontal Blinds




The Blind Factory * 5277 S. Florida Ave. * Lakeland, FL 33813 * (863) 646-8891 * (800) 662-3955 * Fax (863) 701-0889

Congratulations. You have purchased a FineCraft Horizontal Blind, the worlds finest name in custom blinds, shades & shutters. Be sure to ask for genuine FineCraft products whenever needed. Please carefully read the instructions below and fill out and mail the enclosed registration / warranty card. After installation, you will begin enjoying years of service from your FineCraft products. If you have any further questions, please contact your authorized FineCraft dealer.

You will need: A steel tape measure, power drill or screwdriver, #2 square Robertson driver bit, pencil, drill bit.




Step 1) Carefully unpack the FineCraft Blind from the protective packaging being cautious not to cut any of the blind cords. Once unwrapped, snap the clear plastic valance clips over the front edge of metal headrail at each ladder string location as shown.



Step 2) Screw the left and right brackets labeled LH and RH respectively, securely into the window header, window jambs and/ or window frames using the included #2 Robertson Square head screws.



Install the supplied center support(s) for FineCraft Blinds over 70" wide. Blinds over 100" wide include two center supports. Be sure not to mount the support where it will interfere with a ladder location.



cord cleat




Step 3) With the bracket doors open, slide the FineCraft Blind into the brackets and close the bracket doors as shown. Make sure both doors are snapped closed completely.

Step 5) Operate the cord lock to let down the blind. For safety, be sure to keep any cords out of the reach of children and pets using a cord clip or cord cleat. FineCraft Blinds are built to give years of enjoyment! FineCraft Blinds should be kept clean and dusted to maintain the quality factory finish. If you have any questions, please contact your authorized FineCraft dealer.



Step 4) Snap the valance into the valance clips. Release the cord lock to lower the blind.

hold-down bracket



For blinds with optionally ordered hold-down brackets, lower the blind completely and open the slats perpendicular to the mounting surface. Install the brackets to the wall / door surface in alignment with the outside ends of the bottom rail pins.